

LEXAN™ THERMOCLEAR™ 15 **high-performance** panels offer the **Industry's Only 15-Year Warranty** against yellowing and loss of light transmission.

PRODUCT SPECIFICATIONS COMPARISON

8mm and 16mm Lexan™ Thermoclear™ 15 - Clear:

- Made with SABIC Lexan™ resin (Formerly GE Plastics)
- Only 15-Year Prorated Warranty (4% LT loss / 5 yi*)
- Maintains its clarity, strength, and high light levels
- Dripgard coating carries away condensation
- Double-sided UV protection available per request
- Extensive fire and technical reports

Product	Color & LT	Weight	Width	Length
8mm 2-wall	Clear (81%)	.35 lbs/sqft	4' & 6'	48'
16mm 3-wall	Clear (74%)	.57 lbs/sqft	4'	48'

8mm and 16mm Lexan™ Thermoclear™ 15 - Softlite:

- Made with SABIC Lexan™ resin (Formerly GE Plastics)
- Only 15-Year Prorated Warranty (4% LT loss / 5 yi*)
- 100% diffusion to eliminate intensity of sunlight and reduce need for shade
- Dripgard coating carries away condensation
- Double-sided UV protection available per request
- Extensive fire and technical reports

Product	Color & LT	Weight	Width	Length
8mm 2-wall	Softlite (79%)	.35 lbs/sqft	4' & 6'	48'
16mm 3-wall	Softlite (72%)	.57 lbs/sqft	4'	48'

8mm Lexan™ Verolite:

- Made with SABIC Lexan™ resin (Formerly GE Plastics)
- Good 10-Year Prorated Warranty (6% LT loss / 10 yi*)
- Dripgard coating carries away condensation
- Fire and technical reports available

Product	Color & LT	Weight	Width	Length
8mm 2-wall	Clear (81%), Opal (40%), Brz (50%)	.31 lbs/sqft	4', 6' & 71.25"	48'

8mm CoverLite® (GP) General Purpose:

- Strictly commodity sheeting
- 10-Year Prorated Warranty (8% LT loss / 15 yi*)
- Anti-drip coating

Product	Color & LT	Weight	Width	Length
8mm 2-wall	Clear (81%)	.31 lbs/sqft	4', 6' & 71.25"	39'

* Light Transmission (LT) - Percentage of the incident visible light that passes through the sheet.

* Yellowing Index (yi) - A calculated number that specifies the change in color of a test sample from clear or white towards yellow.

A WORLD OF POSSIBILITIES