












AmeriLux International - Architectural Products

March 1, 2017

	Diameter	Product	Structure	Color	U-Value	VLT %	SHGC	Bending Radius	1" Def at 30psf	Warranty & Delta
	6mm (1/4")	THERMOCLEAR™	Twin Wall	Clear	0.62	82	0.82	34"	23" Span	10 Year Δ10
	6mm (1/4")	THERMOCLEAR™	Twin Wall	Opal	0.62	40	0.69	34"	23" Span	10 Year Δ10
	6mm (1/4")	THERMOCLEAR™	Twin Wall	White	0.62	20	na	34"	23" Span	10 Year Δ10
	6mm (1/4")	THERMOCLEAR™	Twin Wall	Bronze	0.62	52	0.58	34"	23" Span	10 Year Δ10
	8mm	THERMOCLEAR™ 15	Twin Wall	Clear	0.57	81	0.82	55"	28" Span	15 Year Δ4
	8mm	THERMOCLEAR™ 15	Twin Wall	Softlite	0.57	79	0.77	55"	28" Span	15 Year Δ4
	8mm	VEROLITE™	Twin Wall	Clear	0.57	81	0.82	55"	28" Span	10 Year Δ10
	8mm	VEROLITE™	Twin Wall	Opal	0.57	40	0.68	55"	28" Span	10 Year Δ10
	8mm	VEROLITE™	Twin Wall	Bronze	0.57	50	0.55	55"	28" Span	10 Year Δ10
	8mm	CoverLite®	Twin Wall	Clear	0.57	81	0.82	55"	28" Span	10 Year Δ10
	10mm (3/8")	THERMOCLEAR™	Twin Wall	Clear	0.52	81	0.8	69"	32" Span	10 Year Δ10
	10mm (3/8")	THERMOCLEAR™	Twin Wall	Opal	0.52	40	0.68	69"	32" Span	10 Year Δ10
	10mm (3/8")	THERMOCLEAR™	Twin Wall	Bronze	0.52	35	0.55	69"	32" Span	10 Year Δ10
	16mm (5/8")	THERMOCLEAR™ 15	3-Wall	Clear	0.40	74	0.78	110"	41" Span	15 Year Δ4
	16mm (5/8")	THERMOCLEAR™ 15	3-Wall	Softlite	0.40	72	0.73	110"	41" Span	15 Year Δ4
	16mm (5/8")	THERMOCLEAR™	3-Wall	Opal	0.40	40	0.57	110"	41" Span	10 Year Δ5
	16mm (5/8")	THERMOCLEAR™	3-Wall	Bronze	0.40	30	0.53	110"	41" Span	10 Year Δ10
	16mm (5/8")	THERMOCLEAR™	3-Wall	White	0.40	20	0.44	110"	41" Span	10 Year Δ10
	16mm (5/8")	THERMOCLEAR™ Sun XP	5x Wall	Clear	0.33	59	58	110"	41" Span	15 Year Δ4
	16mm (5/8")	THERMOCLEAR™ Sun XP	5x Wall	Opal	0.33	51	52	110"	41" Span	15 Year Δ5
	20mm	THERMOCLEAR™ Plus	5x Wall	Opal	0.31	50	0.51	138"	See Guide	10 Year Δ10
	20mm	THERMOCLEAR™ Plus	5x Wall	Clear	0.31	58	0.66	138"	See Guide	10 Year Δ10
	20mm	THERMOCLEAR™ Plus	5x Wall	Bronze	0.31	30	0.45	138"	See Guide	10 Year Δ10
	25mm (1")	THERMOCLEAR™ Plus	5x Wall	Opal	0.27	49	0.54	173"	55" Span	10 Year Δ5
	25mm (1")	THERMOCLEAR™ Plus	5x Wall	Clear	0.27	57	0.65	173"	55" Span	10 Year Δ2
	25mm (1")	THERMOCLEAR™ Plus	5x Wall	Bronze	0.27	50	0.42	173"	55" Span	10 Year Δ5
	25mm	CoverLite®	3-Wall	Clear	0.34	72	0.71	173"	41" Span	10 Year Δ10
	25mm	CoverLite®	3-Wall	Opal	0.34	35	0.51	173"	41" Span	10 Year Δ10
	25mm	CoverLite®	3-Wall	Bronze	0.34	35	na	173"	41" Span	10 Year Δ10
	40mm	THERMOCLICK™	Tongue and Groove	Clear	0.25	59	0.64	na	72" Span	10 Year Δ10
	40mm	THERMOCLICK™	Tongue and Groove	Opal	0.25	50	0.57	na	72" Span	10 Year Δ10
	40mm	THERMOCLICK™	Tongue and Groove	Blue	0.25	20	0.51	na	72" Span	10 Year Δ10
	40mm	THERMOCLICK™	Tongue and Groove	Grey IR	0.25	14	0.32	na	72" Span	10 Year Δ10
	50mm (2")	THERMOCLICK™	T&G 9-Wall	Clear	0.176	0.47	na	na	96" Span	10 Year Δ10
	50mm (2")	THERMOCLICK™	T&G 9-Wall	Opal	0.176	0.45	na	na	96" Span	10 Year Δ10
Lumira Aerogel Filled - Available through consortium members only.										
	10mm (3/8")	THERMOCLEAR™	Twin Wall Lumira® aerogel -filled	Clear	0.33	64	0.64	69	32" Span	10 Year Δ10
	16mm (5/8")	THERMOCLEAR™ Plus	3-Wall Lumira® aerogel-filled	Clear	0.26*	52*	0.57*	110	41" Span	10 Year Δ2
	25mm (1")	CoverLite®	3-Wall Lumira® aerogel-filled	Clear	0.16*	49*	0.54*	173	41" Span	10 Year Δ10
	40mm	THERMOCLICK™	T&G Lumira® aerogel-filled	Clear	0.1*	38*	0.42*	na	72" Span	10 Year Δ10

BOLD* values are Third party tested per NFRC.
 All products Class A & Class CC1 for fire and smoke.
 Loading based on 48" wide sheet supported on four sides.
 THERMOCLICK™ for Vertical Applications Only

THERMOCLEAR, VEROLITE, THERMOCLICK, and LEXAPANEL are trademarks of SABIC