





CoverLite® MR9" and MR12"

Technical and Loading Guidelines

Product	Overall Width	Overall Length	Net Coverage	Pitch	Depth	Thickness	Available Colors
MR9"	38"	Up to 36'	36"	9"	.75"	.035"	Clear, Opal, Bronze & SoftLite
							
MR9" FLAT	38"	Up to 36'	36"	9"	.625"	.035"	Clear & Opal
							
MR12"	38"	Up to 36'	36"	12"	1.25"	.035"	Clear, Opal, Bronze & SoftLite
							
RIDGECAP	24"	10' 6"	—	—	—	.048"	Clear, Opal & SoftLite
 <p>* High Top Profile for Extra Strength</p> <p>24" width 10'6" length 1.2mm thick</p>							

Light Transmission: Clear 90%, Opal 55%, Bronze 35%, SoftLite 85%

Loading Guide: Maximum 50 psf. wind load with 3' on center vertical supports

Purlin Spacing: Maximum horizontal spacing 36" at ridge and gutter and 48" maximum purlin spacing in the mid-span

Pre-Drill Screw Holes: 5/64" larger than screw size to allow for expansion and contraction of panel

Screws & Washers: Use 1" or 2" #10 Woodmate w/wing or 1" or 2" #12 Self-Drilling/Self Tapping screw with a minimum 1/2" neoprene bonded washer

Material Weight: .24 lbs/sq.ft.

