

Description

Lexan Soft Lite LCS100 sheet is a diffused corrugated panel (color number WH9D464X) utilizing advanced polymer technology to scatter light while maintaining high levels of light. This diffusion feature is an excellent candidate for Greenhouse applications, where plants benefit from high levels of light for growth, but need protection from harsh intense sunlight. The scattering of light also improves exposure of low plants and leaves to light, reducing shadows and improving overall plant growth and uniformity.

Lexan Soft Lite LCS100 sheet offers additional features of long term weathering (UV protection), excellent impact resistance, and a ten year limited written warranty.

Typical Property Values ♦

Property	ASTM Test Method	Units (USCS)	Value
Physical			
Specific Gravity	ASTM D792A	--	1.2
Weight**	--	lb/sf	0.25
Light Transmission	ASTM D1003	%	84
PAR Light Transmission	ISO 9050	%	85
Haze (Diffusion)	ASTM D1003	%	100
Corrugation Height	--	mm	76
Corrugation Pitch	--	mm	16
Mechanical			
Tensile Strength	ASTM D638	psi	9,500
Flexural Strength	ASTM D790	psi	13,500
Flexural Modulus	ASTM D790	psi	340,000
Dynatup Impact Strength, (1/2 in Diameter Dart -Gauge Dependent)**	ASTM D3763	ft-lbs	15
Gardner Impact Strength (Gauge Dependent)**		in-lbs	>240
Thermal			
Coefficient of Thermal Expansion	ASTM D696	in/in/°F	3.75x10 ⁻⁵
Solar Heat Gain			0.8
Compliance			
Flammability Burn Class	ASTM D635		CC1

- ♦ These are typical properties and are not intended for specification purposes. If minimum certifiable properties are required, please contact your local SABIC Innovative Plastics, Specialty Film & Sheet representative or the Quality Services Department.
- ** Reported values based on 0.125" average thickness
- * Trademarks of SABIC Innovative Plastics IP BV

Product Availability

Product code:	Lexan* LCS100-WH9D464X
Textures:	Not available
Gauge:	0.03"
Standard Widths:	50 inches and 74 inches
Standard Length:	576 inches
Available Length:	600 inches max
Drip Guard Coating:	LC100DG-WH9D464X

Contact us

SABIC Innovative Plastics
Specialty Film & Sheet
One Plastics Avenue
Pittsfield, MA 01201

Email

tech.service@ameriluxinternational.com



1212 Enterprise Drive, DePere, WI 54115

Tel: 920-336-9300 • 888-602-4441

Fax: 920-336-9301 • www.ameriluxinternational.com

SABIC Innovative Plastics Global Disclaimer

THE MATERIALS, PRODUCTS AND SERVICES OF SABIC INNOVATIVE PLASTICS HOLDING BV, ITS SUBSIDIARIES AND AFFILIATES ("SELLER"), ARE SOLD SUBJECT TO SELLER'S STANDARD CONDITIONS OF SALE, WHICH CAN BE FOUND AT <http://www.sabic-ip.com> AND ARE AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION OR RECOMMENDATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SELLER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING SELLER'S PRODUCTS, SERVICES OR RECOMMENDATIONS. EXCEPT AS PROVIDED IN SELLER'S STANDARD CONDITIONS OF SALE, SELLER SHALL NOT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user is responsible for making its own determination as to the suitability of Seller's products, services or recommendations for the user's particular use through appropriate end-use testing and analysis. Nothing in any document or oral statement shall be deemed to alter or waive any provision of Seller's Standard Conditions of Sale or this Disclaimer, unless it is specifically agreed to in a writing signed by Seller. No statement by Seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Seller or as a recommendation for the use of such product, service, or design in a manner that infringes any patent or other intellectual property right.

SABIC Innovative Plastics is a trademark of SABIC Holding Europe BV

* Trademarks of SABIC Innovative Plastics IP BV

© Copyright 2008. All rights reserved.